

linked by electric means to the actuation means for the second knife in order to release the second knife upon reaching a predetermined sod length.

2. (Amended) Device according to claim 1 wherein the sensor is linked to the actuation means (42, 44,45) via a central processing unit (100).

3. (Amended) Device according to claim 2 wherein the electronic sensor contains a measuring wheel (81) to rest on and to be driven by a passing sod, and that a sensor (82) linked to the measuring wheel records a rotation of the measuring wheel and produces an electronic signal.

4. (Amended) Device according to claim 4 wherein the sensor (82) is capable of recording a rotation direction of the measuring wheel (81).

5. (Amended) Device according to claim 3 wherein the sensor includes an incremental pulse generator.

6. (Amended) Device according to claim 1 wherein electronic detection means (90) are applied to record the presence of a sod in the conveyor track (6) and to produce this as an electronic signal.

7. (Amended) Device according to claim 6 wherein the sensor is freely suspended in a direction essentially transverse to the conveyor track for the sod in order to be raised from a point of departure when a sod passes, and in that the detection means are linked to a suspension of the sensor.

8. (Amended) Device according to claim 7 wherein the means of detection comprises an electronic switch (90) that is capable of cooperating with the suspension of the sensor (80), at least on leaving its point of departure.

9. (Amended) Device according to claim 1 wherein means (95, 96) are installed next to a conveyor track for the sod in order to determine the thickness of the sod and to produce this as an electronic value.

10. (Amended) Device according to claim 9 wherein the sensor is freely suspended in a direction transverse to the conveyor track and in that the means for determining the thickness of the sod comprise a raise detector that is capable of recording an amount of raising of the sensor and producing this as an electronic value.

11. (Amended) Device according to claim 9 wherein the raise detector contains a slide resistor that is linked to the sensor.

12. (Amended) Device according to claim 1 wherein the first knife (21) is adjustable and is equipped with adjustment means (23, 24,25) that can be controlled by a central processing unit (100).

13. (Amended) Device according to claim 12 wherein the means of adjustment contains an electronically controlled actuator (25) connected to the first knife.

14. (Amended) Device according to claim 1 wherein the electronically controlled mechanisms for the second knife (22) contains an electronic clutch (45) that is incorporated in a transmission between a drive (44) for the chassis and a cam disc (42) on which the second knife rests under spring (41) pressure.

---